Description

Radio module

5

The invention relates to a radio module having a radio
device, an internal microprocessor device connected to
the radio device and an interface which is connected to
the microprocessor device and has connection pins for
10   connecting the radio module to at least one external
electrical apparatus, where the radio module is
designed such that it has at least two modes of
operation in which it can be operated, specifically a
passive mode of operation, in which an external
15   microprocessor device is connected to the radio module
as an external electrical apparatus, the radio module
is used as a modem for the external microprocessor
device, and the radio module can be actuated by the
external microprocessor device using modem actuation
20   signals, preferably AT commands, and at least one
active mode of operation, in which at least one
actuator or sensor is connected to the radio module as
an external electrical apparatus, the radio module
actuates and/or reads the at least one actuator or
25   sensor and for its part can be actuated externally via
the radio device.

A radio module of this type is sold by the company
Wavecom under the product name WismoPac. This
30   previously known radio module can be operated in two
modes of operation, specifically in a first mode of
operation, in which the radio module operates as a
modem, and in a second mode of operation, in which the
modem is used in a telecommunication terminal - for
35   example a mobile phone - and undertakes all control
functions therein. The previously known radio module
has an interface with 222 connection pins, among which
a first group of connection pins forms a serial
interface, namely an RS-232 interface, for modem

operation using AT commands. All other connection pins form a second group of connection pins which are responsible for all other tasks of the previously known module, for example for the connection of microphones, loudspeakers, SIM cards or other components.

The invention is based on the object of specifying a radio module which requires as few connection pins as possible.

Against the background of a radio module of the type specified above, the invention achieves this object by virtue of the electrical assignment of the connection pins being designed to be reconfigurable such that the microprocessor device uses at least one connection pin both for the passive mode of operation and for at least one of the active modes of operation.

A fundamental advantage of the radio module according to the invention is that it can be manufactured particularly inexpensively; this is because the inventive radio module requires significantly fewer connection pins for the interface than previously known radio modules, which reduces costs for materials and manufacture. The inventive radio module achieves this specifically by virtue of the connection pins of the interface being available not exclusively for one respective mode of operation of the radio module, but rather - at least to some extent - being able to be used selectively by two or more modes of operation. In this context, the invention makes use of the insight that the inventive radio module is always operated exclusively in a single mode of operation at any time; hence, appropriate actuation or appropriate reading of the connection pins of the interface makes it possible to ensure at all times that each mode of operation of the radio module has its required number of connection pins and the required assignment of the connection pins available.

In line with one development of the inventive radio
module, it is considered to be advantageous if the
microprocessor device is programmed with at least two
5 software programs, among which one software program
forms the operating system of the radio module, which
stipulates the electrical assignment of the connection
pins for each of the at least two modes of operation of
the radio module, and at least one further software
10 program forms application software - that is to say
software which is to be regulated by the user of the
radio module - which stipulates the respective mode of
operation of the radio module. Splitting the
microprocessor software into at least two separate
15 software programs means that the application software
generated by the user of the radio module is separated
from the actual operating system of the radio module in
terms of programming. The electrical assignment of the
connection pins therefore cannot be altered
20 unintentionally by the application software of the user
of the radio module.

For the rest, it is regarded as advantageous if the
user of the radio module is unable to reprogram the
25 connection pins or to alter the assignment of the
connection pins; this can be achieved if just the
application software can be altered externally by the
user, whereas the operating system cannot be altered by
the user.
30

It is a particularly simple and thus advantageous
matter to prevent the user from altering the operating
system by virtue of the operating system being formed
by firmware.
35

It is a simple and thus advantageous matter for the
inventive radio module to be programmed by the user if
the application software is interpreter software which
is preferably based on one of the two programming

languages Basic or Java®. "Java®" is a registered mark belonging to Sun Microsystems, Inc., Palo Alto, USA.

In many countries, official permits are required before
5 radio devices may be operated. To ensure that an official permit obtained for the inventive radio module is not put at risk by virtue of the application software of the user altering the electrical properties of the radio module such that the radio module is no
10 longer under the official permit, it is regarded as advantageous if the application software and the operating system are separate from one another such that the radio device and the interface may be actuated exclusively by the operating system, and the
15 application software is able to access the interface and the radio device exclusively under the switching and control of the operating system, and the application software is prevented from accessing the interface and the radio device directly. In other
20 words, this design of the radio module thus prevents the operating system of the radio module from being able to be altered by the user using his application software; permit problems on account of the application software of the customer are thus reliably prevented.
25 In specific terms, this is because exclusively the permanently preprogrammed operating system of the radio module stipulates the configuration of the interface and the connection assignment of the connection pins; the application software of the user then merely
30 selects a respective one of the configurations permanently prescribed by the operating system; it is not possible for the application software to access the configuration of the radio module or the radio device in the radio module directly.
35

Since the passive mode of operation, that is to say the modem mode of operation, does not require application software from the user, it is regarded as advantageous if the passive mode of operation of the radio module is

stored entirely in the operating system of the radio
module.

To explain the invention,

5   Figure 1 shows an exemplary embodiment of an inventive
radio module which is operated in the passive mode of
operation,
Figure 2 shows the radio module shown in figure 1 in an
active mode of operation,
10 Figure 3 shows a schematic illustration of the division
of the microprocessor software into operating system
software and application software, and
Figure 4 shows a table with an exemplary embodiment of
an assignment of the connection pins in the case of an
15 interface with 19 connection pins.

Figure 1 shows a radio module 5 with a radio device 10,
a microprocessor device 20 and an interface 30. The
radio device 10 is connected to the microprocessor
20 device 20, which is also connected to the interface 30.
The interface 30 has connection pins S1, S2, ..., S8
which can be used to connect the radio module 5 to
external electrical apparatuses.

25 In the illustration shown in figure 1, the radio module
5 is operated as a modem, that is to say in a passive
mode of operation. For this, an external computer 50 is
connected to the interface 30 of the radio module 5.
The electrical connection between the interface 30 and
30 the external computer 50 is ensured by a subgroup 60 of
the connection pins, namely by the connection pins S1,
S2, S3 and S4. This subgroup 60 is used to interchange
"AT commands" between the radio module 5 and the
external computer 50 in order to operate the radio
35 module 5 as a modem.

For reasons of clarity, figure 1 shows only four
connection pins (S1 to S4) for the connection between
the external computer 50 and the radio module 5; it

should be pointed out that the number of connection pins is arbitrary, as it were, and is dependent only on the specific technical configuration of the data connection between the radio module 5 and the external
5   computer 50. By way of example, the number of connection pins for the modem connection may also be nine (cf. the explanations with regard to figure 4, for example).

10 Figure 2 shows the radio module 5 shown in figure 1 in an active mode of operation; specifically, the radio module 5 in the illustration shown in figure 2 is being operated in a communication terminal. For this, a loudspeaker 100 as an actuator, a microphone 110 as a
15 sensor, a display device 120 and a dialing keypad 130 are connected to the connection pins S1 to S8 of the interface 30.

In figures 1 and 2, the connection pins S1 to S4 are
20 seen to be used twice; this is because in modem operation - as shown in figure 1 - they are used to transmit AT commands and - as shown in figure 2 - they are also used to connect actuators and sensors in the case of an active mode of operation.
25
Figure 3 shows a schematic illustration of the radio module 5 from the "software end". Specifically, it is possible to see a block 200 which represents the application software of the radio module 5. In this
30 context, application software is understood to mean that software which a user of the radio module 5 can implement. The application software 200 is connected to the operating system 250 of the radio module 5. In the exemplary embodiment shown in figure 3, the operating
35 system is formed by "firmware", that is to say permanently preprogrammed software which cannot be altered by the user. The firmware may be implemented in ROM chips, for example in EPROM chips.

In the exemplary embodiment shown in figure 3, the operating system 250 is controlling the interface 30 as an I/O device, the radio device 10 and a memory 300 in the microprocessor device 20; this is marked in figure
5   3 by bold solid double-headed arrows.

In the illustration shown in figure 3, external appliances 400 are connected to the interface 30.

10 The application software 200 can never access the interface 30, the radio device 10 and the memory 300 directly, but rather only as a result of switching of the operating system 250; this is illustrated in figure 3 by thin, dashed double-headed arrows.
15

The operating system 250 of the radio module 5 thus stipulates how the connection pins S1 to S8 of the interface 30 are to be used. To this end, the operating system contains various prescribed configurations -
20 specifically in the form of firmware - which stipulate when what connection pins of the interface 30 are to be used in what respective manner.

The specific appearance which the assignment of the
25 connection pins may have - by way of example - is shown by the table which is shown in figure 4 with reference to an exemplary embodiment of an interface 30 equipped with 19 connection pins.